Make a Hidden Slip Stitch on a Fold

A folded-edge practice sample with measured pickup points and a visible thread-route map

What a slip stitch hides

A slip stitch can fasten a folded cloth edge while keeping most of its thread inside the fold. The needle slips along a small channel in the folded edge, then catches a very small amount of the underlying fabric. When the thread is compatible and the tension is gentle, little thread may show on the outer face. That is a technique goal, not a guarantee of invisibility on every material. It differs from a ladder stitch between two separate folded edges, which is not the specific practice layout in this guide.

The exercise uses a base piece of plain woven fabric plus a separate strip with one long edge turned under. It is a low-stress tabletop sample, not the finishing of a valuable garment, a child-safe toy, a protective seam or an archival fabric repair. The two templates let the learner mark the cloth with a ruler before the needle touches it. Steadleaf Press has not folded fabric, pierced it, stitched a sample or tested appearance or durability.

Read the geometry, not just a thumbnail

The full-size base reference is 160 mm wide and 90 mm high. Its horizontal guide sits at y = 45 mm measured from the lower edge. The separate strip begins as a 160 x 45 mm rectangle; fold 12 mm of ONE long edge to the reverse, leaving a nominal visible band 33 mm high. Place its CLEAN FOLDED EDGE along y45 on the base, with the band extending upward to y78. Align the long sides and keep the raw strip edge safely away from the working fold. A reader may choose larger surrounding scraps for easier handling, but the example measurements remain the same.

Mark eleven optional positions x = 20, 32, 44, 56, 68, 80, 92, 104, 116, 128 and 140 mm along the folded edge. That is 11 dots separated by 10 intervals, each 12 mm, spanning 120 mm in all. The dots indicate where a tiny underlying-fabric catch may be made; the stitch size itself is NOT 12 mm. A needle may travel roughly 6 mm inside the folded channel between picks. The exact number of threads caught in the base is not specified by digital geometry.

Safe setup and real-material limitations

Choose ordinary low-risk woven scraps and a suitable hand needle and one single thread of compatible colour. Bring ordinary scissors, a ruler, a fabric marker with instructions for your textile, small clips if needed, and a stable protected table. Keep spare needles and clips accounted for, do not hold the work against the body, and never push an awl or sewing needle toward your hand. An optional thimble can help if the chosen needle and user call for it.

Neither printing at Actual Size nor selecting a stated fabric weight guarantees easy piercing, a neat fold or a hidden stitch. Actual tools, fibres, coating, weave and tension matter. Use expendable offcuts and pause if a needle resists, the cloth starts to tear or safe control cannot be maintained.

Make a Hidden Slip Stitch on a Fold

Transfer the two original patterns

Use the A4 or US Letter guide that matches your printing paper; choose 100% / Actual Size, not Fit. Measure the 50 mm bar on BOTH pattern pages independently. If it prints at 49 mm, a nominal 160 mm reference has been reduced by a factor of 49/50 to 156.8 mm. That is a calculated caution, not a measured publisher trial. If the ruler bar or cutting outline is incomplete, redraw from the numeric dimensions on suitable scrap.

The first drawing includes an exact base and strip cut-reference frame. The second is deliberately enlarged to show the difference between a hidden run inside the fold and a tiny catch in the base. Do not measure the needle size or the base pickup length off that schematic, and do not cut out its coloured route arrows.

Follow the folded edge - steps 1 to 8

1. On a protected flat worktop, prepare a base scrap at least 160 x 90 mm and a separate strip at least 160 x 45 mm. If you use larger pieces for easier control, keep the measured working rectangle within them.

2. On the strip, lightly mark a 12 mm turn-under line parallel to ONE long edge. Fold that edge to the reverse so the visible strip face measures approximately 33 mm from clean fold to the opposite long edge. Do not cut off the 12 mm turned-under part.

3. Mark the base centreline y45. Put the strip onto the base with its CLEAN FOLDED edge resting directly on that line and its body extending toward the upper side of the base. The upper edge should lie near y78. The turned-under margin stays hidden beneath the strip.

4. Hold the layers with removable clips away from the planned needle route, or ask a competent adult to assist if the layers will not lie still. Do not sew over a clip or leave a pin directed toward the work hand.

5. Mark the eleven x positions from 20 through 140 mm in 12 mm increments as small removable indicators near the fold. These are a rhythm reference, not holes that should be pierced all at once.

6. Prepare one thread and needle as in F043, using a single strand with an ordinary low-load starting knot. Select thread similar in tone to the fabric if the object is intended to look understated. Match the eye to thread; do not force a too-thick thread.

7. Begin inside the folded strip near x20 so the starting knot is hidden in the turn-under, not pulled visibly through the base. Bring the needle to the clean folded edge where the first small base-fibre catch will occur.

8. At the first mark, gently pick only a small amount of BASE cloth immediately beside the fold; lift the needle without making a broad surface stitch across the visible base. If the base yarn cannot be picked safely, pause rather than forcing a tiny point.

Repeat the hidden route - steps 9 to 15

9. Guide the needle back inside the folded edge near the first catch. Carry it approximately 6 mm along the fold channel and exit at a clean position. This small hidden run is a starting illustration, not a scale requirement for all fabrics.

10. Travel toward the next marked pickup at x32 while keeping slack controlled and the thread close to the fold. Take another tiny base-fibre catch, then re-enter the folded channel. Do not create a diagonal thread bridge pulled tight across the surface.

11. Continue from x44 to x140 using the same rhythm: short base catch, short hidden passage inside the fold, then travel gently to the next mark. Eleven pickup positions yield ten 12 mm spaces on the planning line; the number of actual stitches may change if you vary positions.

12. After a few catches, stop and look at the OUTER or right side of the base. A few tiny thread specks may be visible. They do not automatically mean you failed. A pronounced row of long surface stitches suggests the needle is carrying too much base fabric.

13. Look at the fold edge for tiny puckers. Pulling too hard can gather the strip, make a ridge or expose thread; soften tension rather than stretching the textile to conceal it.

14. Finish the practice thread gently inside the folded strip or on its concealed reverse using a suitable small low-load knot. Trim only when the needle is under control. Do not use a sewing-machine backtack or a staple to secure this delicate practice sample.

15. Remove all clips, count the needles and store tools. Record the base and strip fibres, 12 mm planning marks, actual pickup choices, thread colour and any visible surface stitch in the record; record NOT TESTED for any step you skipped.

Read the result without claiming performance

Slip stitch aims to make thread inconspicuous, but not mathematically invisible. A plain loose weave may expose small fibres near each catch; an elastic knit may stretch beyond the assumptions of the original flat diagram. Record what you actually see. If the thread cuts a groove in soft cloth, the tension or needle choice may be unsuitable. Do not pull until failure or assign a holding-force rating to a practice hem.

The technique is not a substitute for the full construction of a pillow, garment or padded toy. A finished item may need closed raw edges, specific seam allowance, turning order, washable materials and a separately appropriate closing method. Choose these from task-specific instructions rather than this small explanatory layout.

Troubleshoot the common visual problems

Thread is visible as long diagonal bridges: shorten the exposed crossing between the fold and base, put more of the needle travel inside the fold, and take smaller surface catches. A ridge appears along y45: reduce pulling and recheck that the strip was turned under 12 mm consistently. The strip begins to twist: confirm that both x edges line up and that no clips are pulling one side more strongly.

The first knot pops out: start deeper in the folded channel with a low-load knot suitable for the actual thread and weave. The base is damaged by a large needle hole: choose a more suitable needle or larger expendable sample; do not heat, glue or cut the fibres to conceal the spot. A marker does not wash out: read the tool label and avoid further marking on valued fabric.

Variation and important exclusions

Some instructions use the term slip stitch for joining two folded edges in a hidden closure; this edition instead attaches ONE folded edge to an underlying base with small catches. These are related but different stitch routes. Do not adapt the enlarged schematic as a load-bearing hidden seam in a bag, strap, pet accessory, medical garment or child article.

If you alter the working strip height or fold-under depth, write a new cut and turn line: for example, a 15 mm turn-under in a 45 mm strip leaves a 30 mm visible band. That arithmetic is a design variation, not an approval that thicker folded materials will lie flat. No physical fabric and needle trial was performed by Steadleaf Press.

Sources, originality and disclosure

Oregon State University Extension, Hand-Sewing Skills: Level 1: https://extension.oregonstate.edu/sites/extd8/files/documents/4-h320-13.pdf . Explains conventional slip-stitch uses; no figures from that source are reproduced.

4-H Ontario, Sewing - Sewing Plus Project: https://4-hontario.ca/wp-content/uploads/2022/01/Sewing-Sewing-Plus-Project.pdf . General background for short passes inside a fold and tiny underlying catches; not an endorsement of this geometry.

Adobe Acrobat Help, PDF print page size: https://helpx.adobe.com/acrobat/desktop/print-documents/set-up-and-print-pdfs/page-size.html . Used only for Actual Size versus Fit printing.

The two measured templates, eleven-mark placement map, step explanation, illustration, cover and records are original Steadleaf Press digital assets. No commercial sewing template, photograph or third-party artwork is included. No physical printing, folding, stitching, tensile, wash, safety or durability test was performed.

TWO FULL-SIZE SLIP-STITCH FABRIC REFERENCES

BASE 160 x 90 mm / centre guide at y45



TOP STRIP 160 x 45 mm / 12 mm turn-under



After folding, visible face is nominally 33 mm high.



50 mm SCALE CHECK - measure the printed line with a physical ruler

HIDDEN PASSAGE AND TINY BASE CATCHES

FOLD FACE / TRAVEL INSIDE THE TURNED EDGE



BASE CLOTH / very small fibre picks beneath fold

1. Hide the starter knot inside the folded strip.
2. Catch 1-2 tiny base fibres at the edge.
3. Enter fold; carry thread about 6 mm inside.
4. Move gently to next marker, repeat.
5. Avoid long front thread bridges and puckering.



50 mm SCALE CHECK - measure the printed line with a physical ruler

MAKER RECORD / DECISIONS AND DIMENSIONS

Base 160 x 90, strip 160 x 45 mm

Fold-under depth 12 mm / visible face 33 mm

Clean fold aligned to base y45

x20..140 at 12 mm / 11 pickup positions

Actual printer page and 50 mm measurements

Needle, thread, fabric and marker used

Visible base catches and fold appearance

Physical trial performed? NO / details if actually made

Record measured outcomes only if you actually made a sample.

Publisher performed NO physical printing, stitching, tensile, fit or safety test.



50 mm SCALE CHECK - measure the printed line with a physical ruler

MAKER RECORD / OUTCOME, LIMITS AND NEXT VERSION

What did you observe on your own physical sample, if any?

Where did measurement or transfer differ from the digital pattern?

Which part of the needle or fold route needs clarification?

What was left NOT TESTED? Do not invent a result.

What material, tool or tension would you change next?

What actual safe handling or storage issue arose?

Does the chosen use exceed this low-risk teaching purpose?

Date, initials, revision number and next action

Record measured outcomes only if you actually made a sample.

Publisher performed NO physical printing, stitching, tensile, fit or safety test.



50 mm SCALE CHECK - measure the printed line with a physical ruler