
Repair a Loose Hem

Keep the original fold depth and length



Inside view • blue: folded hem • green: sound stitching

Restore a short accessible folded hem using small hand stitches with minimal show on the face.

14 practical steps • Original diagrams and repair records

Illustrative repair plans — not physical test results

Before you start

A hem can come loose when its thread breaks even though the fold and fabric are sound. Restore the original fold instead of trimming cloth or changing the garment length. This guide covers a short loose, turned hem in ordinary adult nonstretch woven clothing, where the fold and any raw-edge finish remain intact. It does not cover tailored invisible hems with unfamiliar layers, stretch hems, bonded hems or safety clothing.

Materials

Garment, fine suitable hand needle, compatible thread, ruler, clips or pins, removable marking tool, scissors, comparable scrap and a thimble if appropriate. Use a bright clean work surface. Avoid heat if the garment care label does not permit it. Keep needles and pins accounted for and work off the body.

Plan the repair

The example has a 40 mm loose segment of an existing double-fold hem with a 20 mm finished depth. Preserve the actual original fold depth, edge finish and garment length. Mark the two ends and include about 10 mm of sound attachment on each side if accessible, making an example worked span of 60 mm. From the inside, anchor in the fold and use a slip stitch: take a tiny bite of the main garment fabric close to the upper folded edge, then travel inside the folded edge and emerge a few millimetres ahead. Repeat without drawing the fold tight. About 4 mm between face-fabric bites is a starting example; match the material. If the fold is torn, raw or structurally different, refer or choose a suitable edge-repair method.

Steps 1–2

1. Identify the loose section

Lay the garment flat and locate the part where the hem has separated from the main fabric. Check the cloth and existing fold are sound, with no widespread abrasion, cut edge or unusual finish. Confirm it is an ordinary woven garment.

2. Read the existing hem

Look from the inside at a sound section next to the opening. Identify the fold, where the thread catches the garment and the original hem depth. If the construction is bonded, stretchy or inaccessible, use another method.

Steps 3–4

3. Record the original length

Measure from a stable nearby reference such as a side seam or the intact hem. Record the depth and loose length: 20 mm and 40 mm in the example. Do not cut the garment or add a new fold just to make the loose portion even.

4. Inspect the raw-edge finish

Check whether the upper edge is already folded under or otherwise safely finished. This guide assumes an intact double-fold upper edge suitable for hiding the travelling thread. A frayed open edge needs separate stabilization.

Steps 5–6

5. Choose needle and thread

Select a fine compatible hand needle and thread that will not enlarge holes or create visible bulk. Match colour and care to the garment. Practise on similar cloth before trying to catch a single small face-fabric bite.

6. Practise a slip stitch

Fold comparable scrap and anchor the thread inside the upper fold. Take a tiny bite of the main fabric just above the fold, then enter the fold close to that bite and travel along it before emerging roughly 4 mm ahead.

Steps 7–8

7. Remove only failed thread

Carefully remove loose broken attachment threads that interfere with alignment. Preserve sound stitching and the fold’s edge finish. If thread cannot be separated from fabric yarns, stop instead of cutting blindly.

8. Align the old crease

Turn the hem to its original position, checking the depth against adjacent sound hem. Hold it flat with clips or pins placed away from the path. Use pressing only if permitted by care instructions, and avoid flattening decorative texture.

Steps 9–10

9. Mark the worked span

Mark the start and finish about 10 mm into sound attached hem where accessible. The 40 mm gap plus two 10 mm overlaps gives about 60 mm. Confirm the overlap does not cross into an inaccessible seam or different construction.

10. Anchor in the fold

With the garment inside out, secure a short thread inside the folded upper edge near the first overlap. Keep the tail hidden within the fold. Bring the needle out close to where the fold meets the main fabric.

Steps 11–12

11. Work the slip stitches

Pick up a very small bite of the main fabric above the fold; do not pierce a second unrelated layer. Insert into the folded edge near that bite, move along inside it and emerge a few millimetres ahead. Repeat across the opening with relaxed tension.

12. Finish and secure

Continue into the sound hem at the far end, then anchor the thread within the fold with small securing stitches. Trim carefully. Remove clips and pins and check that the fold has not rolled or shifted.

Steps 13–14

13. Inspect both sides

Compare the new section with the adjacent intact hem. The outer face should not show a line of large stitches or puckers. Check the relaxed length is unchanged and the hem moves freely. If the fold pulls or drops, revise before wear.

14. Record and maintain

Record the actual hem depth, worked span, stitch spacing and observed result. Follow the garment's care label and check after normal use. A nearly invisible finish is a goal, not a guarantee of appearance or durability.

Fix, care and preserve

Face stitches are too visible

Use a smaller bite of main fabric and a compatible fine thread.

Hem pulls upward

Release tight stitches; restore the original crease and relaxed garment length.

Fold edge frays

Stop and choose an appropriate edge-stabilizing method before reattaching.

Repair opens at an end

Check that attachment reaches sound material; refer if the surrounding hem has deteriorated.


Originality and evidence boundary

Original Steadleaf English prose, design, artwork, diagrams and repair records. Follow actual garment, material and tool instructions. No physical sewing, washing, durability, strength or safety testing was performed by the publisher. Adult ordinary-clothing mending only; no safety or performance certification.

Print the following pages separately if desired. Measured schematics are not full-size cutting patterns. Record only actual observations.

Pattern 1

Hem restoration map: 40 mm loose segment plus 10 mm overlap on either side (60 mm worked span); existing example hem depth 20 mm. Preserve actual fold and garment length. Schematic.




Inside view • blue: folded hem • green: sound stitching

Pattern 2

Slip stitch detail, inside view: tiny bite in main fabric adjacent to upper folded edge, then hidden thread travel inside the fold to emerge about 4 mm ahead. Do not pull the fold tight. Enlarged schematic.

Slip stitch • inside view, enlarged



Do not tighten the fold against the main fabric.

Record 1 — Materials and repair plan

Record actual observations only. Use UNKNOWN or NOT CHECKED for anything you have not established.

Garment / fabric / care instructions

Original hem construction and depth

Loose length / intact reference

Raw-edge finish / cloth condition

Needle and thread / practice result

Planned overlap and stitch spacing

Pressing and access limits

Decision: PROCEED / CHANGE / REFER

Record 2 — Finish and follow-up

Record actual observations only. Use UNKNOWN or NOT CHECKED for anything you have not established.

Actual worked span / depth

Fold alignment / garment length

Visible face stitches / puckering

Reverse anchors / tool count

Gentle movement observation

Remaining damage / care restrictions

Decision: ORDINARY USE / CHANGE / REFER

Date / follow-up